

MERLIN EXTREME DUTY INVERTERS [1000W - 1800W]

Merlin Extreme Duty Inverters utilise hybrid power conversion technology to provide significant benefits over low-cost, leisure style, switch-mode inverters and are designed specifically for mission critical applications where lives and livelihoods depend on power.

Designed & manufactured in Europe, Merlin Extreme Duty Inverters are built with leading brand components to provide a superlative inverter that outperforms all others and last years in everyday applications. Merlin Extreme Duty Inverters carry a full 5 year warranty.

Merlin Extreme Duty Inverters are highly configurable. Using simple windows-based software, an internal relay can be set-up to activate external devices (such as an automatic generator start facility) when any internal alarm is triggered. Various set points and configurable neutral/earth bonding ensures that you are able to conform to 18th Edition wiring regulations. Automotive e-mark also ensures legal fitting aboard road-going vehicles.

- **Significantly improved reliability** which is translated to the warranty term of 5 years.
- **High performance** in their ability to provide greater than their rated output for lengthier periods of time.
- **Withstands inductive AC loads** without inverter damage.
- **Advanced protection** against short circuits, overloading, and high temperatures.
- **Wide variety of sizes** combined with the robust industrial design, helps in finding the right model for every application.



PART#	30-1014	30-1018	30-1016	30-1020
RATING	1000W, 12V	1600W, 12V	1400W, 24V	1800W, 24V
AC OUTPUT				
OUTPUT POWER (CONTINUOUS)	850W	1300W	1000W	1400W
OUTPUT POWER (10 MINS)	1050W	1600W	1450W	1800W
OUTPUT POWER (SURGE)	2000W	2500W	2800W	3000W
OUTPUT VOLTAGE/FREQUENCY	230V AC \pm 2% 50HZ \pm 0.05%	230V AC \pm 2% 50HZ \pm 0.05%	230V AC \pm 2% 50HZ \pm 0.05%	230V AC \pm 2% 50HZ \pm 0.05%
OUTPUT WAVEFORM	TRUE SINEWAVE (THD <5%)	TRUE SINEWAVE (THD <5%)	TRUE SINEWAVE (THD <5%)	TRUE SINEWAVE (THD <5%)
PEAK EFFICIENCY	92%	92%	92%	92%
DC INPUT				
VOLTAGE (NOMINAL)	12VDC	12VDC	24VDC	24VDC
OPERATION RANGE	10 . 52VDC - 16 vDc	10. 52VDC - 16VDC	21VDC - 32VDC	21VDC - 32VDC
CURRENT (NO LOAD, ASB)	<9.6W [2.5W]	<9.6W [2.5W]	<12W [3.5W]	<12W [3.5W]
ASB THRESHOLD	POUT=10W	POUT=10W	POUT=10W	POUT=10W
TEMPERATURE				
OPERATING TEMP. RANGE	-20°C ... +50°C	-20°C ... +50°C	-20°C ... +50°C	-20°C ... +50°C
STORAGE TEMP. RANGE	-40°C ... +80°C	-40°C ... +80°C	-40°C ... +80°C	-40°C ... +80°C
COOLING	VARIABLE SPEED FAN	VARIABLE SPEED FAN	VARIABLE SPEED FAN	VARIABLE SPEED FAN
PROTECTION				
LOW BATTERY VOLTAGE	YES	YES	YES	YES
OUTPUT SHORT CIRCUIT	YES	YES	YES	YES
HIGH TEMPERATURE	YES	YES	YES	YES
OVERLOAD	YES	YES	YES	YES
INDICATIONS				
POWER ON	YES	YES	YES	YES
OUTPUT POWER BAR	YES	YES	YES	YES
ERROR	YES	YES	YES	YES
ASB MODE	YES	YES	YES	YES
ENCLOSURE				
DC INPUT CONNECTIONS	2 X 25MM ²	2 X 35MM ²	2 X 25MM ²	2 X 35MM ²
AC OUTPUT CONNECTIONS	SCREW TERMINALS	SCREW TERMINALS	SCREW TERMINALS	SCREW TERMINALS
DIMENSIONS (MM)	351 X 210 X 114	351 X 210 X 114	351 X 210 X 114	351 X 210 X 114
WEIGHT (KG)	10.2	10.5	10 .2	10.5
PROTECTION CLASS	IP21	IP21	IP21	IP21
STANDARDS	CE MARK MEETING EMC DIRECTIVE 2004/1008/EC & LVD 2006/95/EC COMPLYING WITH EN60335-1, E4-95/54/ EC, ROHS 2002/95/EC			